



## LED DRIVER PRODUCT LIST

CONSTANT VOLTAGE DRIVERS											
MX PN	Standards	Power (W)	Output voltage (V)	Output current (mA)	Input Voltage (V)	Dimmable	Programmable	PF	Efficiency %	size (L*W*H) mm	Protection Rating
MXLFCV012012002AE	CE	12	12	1000	198-264	none	none	0.8	80	98x39x22	IP20
MXLFCV020012002AE	CE	20	12	1670	198-264	none	none	0.8	82	113x44x28	IP20
MXLFCV020024002AE	CE	20	24	830	198-264	none	none	0.8	84	113x44x28	IP20
MXLFCV036012007AE	CE	36	12	3000	90-264	none	none	0.9	82	169x55x30.5	IP67
MXLFCV036024007AE	CE	36	24	1500	90-264	none	none	0.9	84	169x55x30.5	IP67
MXLFCV050012002AE	CE	50	12	4150	90-264	none	none	0.9	82	184x61x32	IP20
MXLFCV050024002AE	CE	50	24	2100	90-264	none	none	0.9	84	184x61x32	IP20
MXLFCV060012005AE	CE	60	12	5000	90-264	none	none	0.95	84	240x30x28	IP65
MXLFCV060024005AE	CE	60	24	2500	90-264	none	none	0.95	87	240x30x28	IP65
MXLFCV075024007AE	CE	75	24	3150	90-264	none	none	0.95	85	202x64x40	IP67
MXLFCV100012007AE	CE	100	12	8300	198-264	none	none	0.95	91	191x70x40	IP67
MXLFCV100024007AE	CE	100	24	4200	198-264	none	none	0.95	91	191x70x40	IP67
MXLFCV150012007AE	CE	150	12	12500	90-264	none	none	0.95	90	223x70x40	IP67
MXLFCV150024007AE	CE	150	24	6300	90-264	none	none	0.95	90	223x70x40	IP67
MXLFCV200012007AE	CE	200	12	16600	198-264	none	none	0.95	91	249x70x40	IP67
MXLFCV200024007AE	CE	200	24	8300	198-264	none	none	0.95	93	249x70x40	IP67

CONSTANT CURRENT DRIVERS											
MX PN	Standars	power	current rating (mA)	Output voltage range	Input Voltage (V)	Dimmable	Programmable	PF	Efficiency %	size (L*W*H) mm	Protection Rating
MXLFC009035T02AE	CE	9	350	13 - 26	198-264	Triac	none	0.95	80	112x40x22	IP20
MXLFC018035T02AE	CE	18	350	26 - 52	198-264	Triac	none	0.95	83	120x45x28	IP20
MXLFC018050T02AE	CE	18	500	18 - 36	198-264	Triac	none	0.95	83	120x45x28	IP20
MXLFC018070T02AE	CE	18	700	13 - 26	198-264	Triac	none	0.95	83	120x45x28	IP20
MXLFC018105T02AE	CE	18	1050	9 - 17	198-264	Triac	none	0.95	83	120x45x28	IP20
MXLFC028XV02AE	CE	28	350/500/700	10 - 80	90-264	0-10V	none	0.95	82	210x31x22	IP20
MXLFC028XA02AE	CE	28	350/500/700	10 - 80	90-264	Dali	none	0.95	83	210x31x22	IP20
MXLFC0401050V02AE	CE	40	1050	18-56	198 - 264	1-10V	none	0.95	85	139x75x30	IP20